ELECTRIC SOUND
premium brands & added value

Electric Sound Benelux B.V.
The Netherlands
Radioweg 5
1324 KW Almere (NL)
Tel. +31 (0)36 54 600 20
Fax. +31 (0)36 54 600 29

Belgium & Luxembourg
Weihoek 3, Unit 5
1930 Zaventem (BE)
Tel. +32 (0)2 788 73 00
Fax. +32 (0)2 788 73 01

BEYERDYNAMIC PRO HEADPHONES AND HEADSETS

LISTPRICING 01-06-2010

				NEDERLAND	BELGIE	LUXEMBURG
			EURO	EURO	EURO	EURO
art.nr.	**ARTICLE**	**DESCRIPTION**				
			excl.BTW	incl.19% BTW	incl.21% BTW/TVA	incl.15% BTW/TVA
		DYNAMIC HEADPHONES				
15851	**DT 60 PRO B #**	In-ear headphones, 16 Ω, 106 dB, closed, neodynium magnet, stereo mini-jack, incl. silicone ear plugs in different sizes, mini-bag and cable clip, black	48,74	58	59	56
15762	**DT 60 PRO SC #**	In-ear headphones, 16 Ω, 106 dB, closed, neodynium magnet, stereo mini-jack, incl. silicone ear plugs in different sizes, mini-bag and cable clip, skin colour	48,74	58	59	56
14300	**DT 48 A.00**	Audiometry headphones, 5 Ω, closed systems, with cable K 48.00 (free ends)	328,99	392	398	378
14301	**DT 48 E**	Professional headphones, 25 Ω, closed systems, with single sided coiled cable WK 48.07 E (stereo mini-jack / 1/4" adapter)	328,99	392	398	378
14303	**DT 48 E**	Professional headphones, 200 Ω, closed systems, with single sided coiled cable WK 48.07 E (stereo mini-jack / 1/4" adapter)	328,99	392	398	378
15525	**DT 100 16 Ω/grey**	Studio headphones, 16 Ω, closed systems, with cable K 100.07 (stereo mini-jack / 1/4" adapter), 3 m (10 ft.), grey	142,56	170	173	164
15421	**DT 100 16 Ω/black**	Studio headphones, 16 Ω, closed systems, with cable K 100.07 (stereo mini-jack / 1/4" adapter), 3 m (10 ft.), black	142,56	170	173	164
15039	**DT 100 400 Ω/grey**	Studio headphones, 400 Ω, closed systems, with cable K 100.07 (stereo mini-jack / 1/4" adapter), 3 m (10 ft.), beige	142,56	170	173	164
15496	**DT 100 400 Ω/black**	Studio headphones, 400 Ω, closed systems, with cable K 100.07 (stereo mini-jack / 1/4" adapter), 3 m (10 ft.), black	142,56	170	173	164
15691	**DT 102 16 Ω/grey**	Studio headphones (single-ear), 16 Ω, closed systems, with cable K 100.07 (stereo mini-jack / 1/4" adapter), 3 m (10 ft.), grey	103,57	123	125	119
15043	**DT 102 400 Ω/grey**	Studio headphones (single-ear), 400 Ω, closed systems, with cable K 100.07 (stereo mini-jack / 1/4" adapter), 3 m (10 ft.), grey	103,57	123	125	119
15044	**DT 150 250 Ω**	Studio headphones, 250 Ω, closed systems, with cable K 100.07 (stereo mini-jack / 1/4" adapter), 3 m (10 ft.), charcoal-grey	159,62	190	193	184
15526	**DT 231 PRO**	Studio headphones, 32 Ω, closed systems, single sided cable (stereo mini-jack / 1/4" adapter)	40,94	49	50	47
14403	**DT 250 80 Ω**	Studio headphones, 80 Ω, closed systems, with coiled cable WK 250.30/07, stereo mini-jack / 1/4" adapter	172,29	205	208	198
14286	**DT 250 250 Ω**	Studio headphones, 250 Ω, closed systems, with coiled cable WK 250.30/07 (stereo mini-jack / 1/4" adapter)	172,29	205	208	198
14400	**DT 252 80 Ω**	Studio headphones (single-ear), 80 Ω, closed systems, with coiled cable WK 250.30/07 (stereo mini-jack / 1/4" adapter)	138,18	164	167	159
15327	**DT 770 M 80 Ω**	Monitoring headphones for drummers and FOH-Engineers, 80 Ω, closed systems, straight single sided cable 3 m (10 ft.), volume control, 105 dB SPL, 35 dBA isolation, with stereo mini-jack / 1/4" adapter	182,77	218	221	210
15477	**DT 770 PRO 80 Ω**	Studio headphones, 80 Ω, closed systems, straight single sided cable 3 m (10 ft.), with stereo mini-jack / 1/4" adapter	164,98	196	200	190
14305	**DT 770 PRO 250 Ω**	Studio headphones, 250 Ω, closed systems, single sided coiled cable, with stereo mini-jack / 1/4" adapter	164,98	196	200	190
15542	**DT 880 PRO 250 Ω**	Studio headphones, 250 Ω, semi-open, single sided coiled cable with stereo mini-jack / 1/4" adapter	255,88	305	310	294
14252	**DT 990 PRO 250 Ω**	Studio headphones, 250 Ω, open systems, single sided coiled cable, with stereo mini-jack / 1/4" adapter	164,98	196	200	190
		DYNAMIC HEADPHONES WITH BUILD-IN LIMITER				
	DT 250 LTD 80 Ω NIEUW	Studio headphones, 80 Ω, closed systems, with coiled cable WK 250.30/07, stereo mini-jack / 1/4" adapter with integrated limiter	224,20	267	271	258
	DT 250 LTD 250 Ω NIEUW	Studio headphones, 250 Ω, closed systems, with coiled cable WK 250.30/07 (stereo mini-jack / 1/4" adapter) with integrated limiter	224,20	267	271	258
	DT 252 LTD 80 Ω NIEUW	Studio headphones (single-ear), 80 Ω, closed systems, with coiled cable WK 250.30/07 (stereo mini-jack / 1/4" adapter) with integrated limiter	190,08	226	230	219
	DT 770 PRO LTD 80 Ω NIEUW	Studio headphones, 80 Ω, closed systems, straight single sided cable 3 m (10 ft.), with stereo mini-jack / 1/4" adapter with integrated limiter	216,89	258	262	249
15838	**DT 770 PRO LTD 250 Ω NIEUW**	Studio headphones, 250 Ω, closed systems, single sided coiled cable, with stereo mini-jack / 1/4" adapter with integrated limiter	216,89	258	262	249
		ACCESSOIRIES FOR DT 48/100/250 HEADPHONES				

14308	**K 100.07 - 3.0 m**	Connecting cable (straight) for DT 100 series with stereo mini-jack / 1/4" adapter	28,68	34	35	33
15878	**K 250.07**	Connecting cable (straight) for DT 250 series with stereo mini-jack / 1/4" adapter	26,81	32	32	31
15604	**WK 48.07 #**	kabel voor DT 48 krul model met 6,3 mm steekplug	30,73	37	37	35
15617	**WK 48.07 E**	Coiled connecting cable for DT 48 E with stereo mini-jack / 1/4" adapter	30,73	37	37	35
14316	**WK 100.00**	Coiled connecting cable for DT 100 series with free ends	28,68	34	35	33
14317	**WK 100.07**	Coiled connecting cable for DT 100 series with stereo mini-jack / 1/4" adapter	30,73	37	37	35
14565	**WK 250.30/07**	Coiled connecting cable for DT 250/252 with stereo mini-jack / 1/4" adapter	30,73	37	37	35
		DT 1XX SERIES HEADSETS				
15701	**DT 108 200/ 50/grey**	Single-ear headset, 200/50 Ω, grey, without cable	136,47	162	165	157
15702	**DT 108 200/ 50/black**	Single-ear headset, 200/50 Ω, black, without cable	136,47	162	165	157
15703	**DT 108 200/400/grey**	Single-ear headset, 200/400 Ω, grey, without cable	136,47	162	165	157
15704	**DT 108 200/400/black**	Single-ear headset, 200/400 Ω, black, without cable	136,47	162	165	157
15705	**DT 109 200/ 50/grey**	Headset, 200/50 Ω, grey, without cable	184,97	220	224	213
15706	**DT 109 200/ 50/black**	Headset, 200/50 Ω, black, without cable	184,97	220	224	213
15707	**DT 109 200/400/grey**	Headset, 200/400 Ω, grey, without cable	184,97	220	224	213
15708	**DT 109 200/400/black**	Headset, 200/400 Ω, black, without cable	184,97	220	224	213
15709	**DT 190 200/250 Ω**	Headset, 200/250 Ω, charcoal-grey, without cable	233,46	278	282	268
		CABLES FOR DT 1XX SERIES HEADSETS				
14309	**K 109.00 - 1.5 m**	Connecting cable for DT 109 series with free ends (standard cable)	26,64	32	32	31
15637	**K 109.00 - 3.0 m**	Connecting cable for DT 109 series with free ends	29,71	35	36	34
15855	**K 109.26 - 1.5 m**	Connecting cable for DT 109 series with 4-pin mini-jack for SONY cameras (DR 100 compatible)	40,97	49	50	47
15725	**K 109.28 - 1.5 m**	Connecting cable for DT 109 series with 4-pin XLR female	43,01	51	52	49
15664	**K 109.38 - 1.5 m**	Connecting cable for DT 109 series with 5-pin XLR male	42,79	51	52	49
15736	**K 109.40 - 1.5 m**	Connecting cable for DT 109 series with 3-pin XLR male and 1/4" stereo jack	53,25	63	64	61
	K 109.42 - 1.5 m	Connecting cable for DT 109 series with 4-pin XLR male	43,01	51	52	49
	K 109.48 - 3.0 m	Connecting cable for DT 109 series with 2 x stereo mini-jack for multimedia applications	46,08	55	56	53
14318	**WK 109.00**	Coiled connecting cable for DT 109 series with free ends	38,92	46	47	45
		DT 2XX and 7XX SERIES HEADSETS				
15075	**DT 234 PRO**	Headset, 32 Ω, closed systems, for all kinds of multimedia applications, equipped with microphone and headphone cables with stereo mini-jacks / 1/4" adapter	80,42	96	97	92
15710	**DT 280 200/80 Ω #**	Single-ear headset, 200/80 Ω, with dynamic microphone (hypercardioid), without cable	188,87	225	229	217
15711	**DT 280 200/250 Ω #**	Single-ear headset, 200/250 Ω, with dynamic microphone (hypercardioid), without cable	188,87	225	229	217
15846	**DT 280 MK II 200/80 Ω NEW**	Single-ear headset, 200/80 Ω, with dynamic microphone (hypercardioid), without cable, with pivoting mic. boom	214,45	255	259	247
15847	**DT 280 MK II 200/250 Ω NEW**	Single-ear headset, 200/250 Ω, with dynamic microphone (hypercardioid), without cable, with pivoting mic. boom	214,45	255	259	247
	DT 280 V.11 MK II 200/80 Ω NEW	Single-ear headset, 200/80 Ω, with dynamic microphone (hypercardioid) and built-in pre-amplifier, without cable, with pivoting mic. boom	214,45	255	259	247
	DT 287 PV MK II 80 Ω NEW	Single-ear headset, 80 Ω, with condenser microphone (cardioid), for phantom power, without cable, with pivoting mic. boom	224,20	267	271	258
	DT 287 PV MK II 250 Ω NEW	Single-ear headset, 250 Ω, with condenser microphone (cardioid), for phantom power, without cable, with pivoting mic. boom	224,20	267	271	258
	DT 287 V.11 MK II 80 Ω NEW	Single-ear headset, 80 Ω, with condenser microphone (cardioid) and built-in pre-amplifier, without cable, with pivoting mic. boom	224,20	267	271	258
15715	**DT 290 200/ 80 Ω #**	Headset, 200/80 Ω, with dynamic microphone (hypercardioid), without cable	220,79	263	267	254
15716	**DT 290 200/250 Ω #**	Headset, 200/250 Ω, with dynamic microphone (hypercardioid), without cable	220,79	263	267	254
15848	**DT 290 MK II 200/80 Ω NEW**	Headset, 200/80 Ω, with dynamic microphone (hypercardioid), without cable, with pivoting mic. boom	253,45	302	307	291
15881	**DT 290 MK II 200/250 Ω NEW**	Headset, 200/250 Ω, with dynamic microphone (hypercardioid), without cable, with pivoting mic. boom	253,45	302	307	291
	DT 290 V.11 MK II 200/ 80 Ω NEW	Headset, 200/80 Ω, with dynamic microphone (hypercardioid) and built-in pre-amplifier, without cable, with pivoting mic. boom	253,45	302	307	291
	DT 291 PV MK II 80 Ω NEW	Headset, 80 Ω, with condenser microphone (omnidirectional), for phantom power, without cable, with pivoting mic. boom	282,69	336	342	325
	DT 291 PV MK II 250 Ω NEW	Headset, 250 Ω, with condenser microphone (omnidirectional), for phantom power, without cable, with pivoting mic. boom	282,69	336	342	325
15720	**DT 297 PV 80 Ω #**	Headset, 80 Ω, with condenser microphone (cardioid), for phantom power, without cable	237,61	283	288	273
	DT 297 PV MK II 80 Ω NEW	Headset, 80 Ω, with condenser microphone (cardioid), for phantom power, without cable, with pivoting mic. boom	263,19	313	318	303
15721	**DT 297 PV 250 Ω**	Headset, 250 Ω, with condenser microphone (cardioid), for phantom power, without cable	237,61	283	288	273
	DT 297 PV MK II 250 Ω NEW	Headset, 250 Ω, with condenser microphone (cardioid), for phantom power, without cable, with pivoting mic. boom	263,19	313	318	303
	DT 297 V.11 MK II 80 Ω NEW	Headset, 80 Ω, with condenser microphone (cardioid) and built-in pre-amplifier, without cable, with pivoting mic. boom	263,19	313	318	303
15840	**DT 790.00 80 Ω**	Headset, 200/80 Ω, with dynamic microphone (hypercardioid), with cable 1,5 mtrs, open end	272,94	325	330	314

		DT 2XX en 7XX SERIES HEADSETS WITH BUILT-IN LIMITER				
	DT 280 MK II LTD 200/ 80 Ω NEW	Single-ear headset, 200/80 Ω, with dynamic microphone (hypercardioid), without cable, with integrated limiter and pivoting mic. boom	287,56	342	348	331
	DT 280 K II LTD 200/250 Ω NEW	Single-ear headset, 200/250 Ω, with dynamic microphone (hypercardioid), without cable, with integrated limiter and pivoting mic. boom	287,56	342	348	331
	DT 287 PV MK II LTD 80 Ω NEW	Single-ear headset, 80 Ω, with condenser microphone (cardioid), for phantom power, without cable, with integrated limiter and pivoting mic. boom	294,87	351	357	339
	DT 287 PV MK II LTD 250 Ω NEW	Single-ear headset, 250 Ω, with condenser microphone (cardioid), for phantom power, without cable, with integrated limiter and pivoting mic. boom	294,87	351	357	339
	DT 290 MK II LTD 200/ 80 Ω NEW	Headset, 200/80 Ω, with dynamic microphone (hypercardioid), without cable, with integrated limiter and pivoting mic. boom	314,37	374	380	362
	DT 290 MK II LTD 200/ 250 Ω NEW	Headset, 200/250 Ω, with dynamic microphone (hypercardioid), without cable, with integrated limiter and pivoting mic. boom	314,37	374	380	362
	DT 291 PV MK II LTD 80 Ω NEW	Headset, 80 Ω, with condenser microphone (omnidirectional), for phantom power, without cable, with integrated limiter and pivoting mic.boom	348,49	415	422	401
	DT 291 PV MK II LTD 250 Ω NEW	Headset, 250 Ω, with condenser microphone (omnidirectional), for phantom power, without cable, with integrated limiter and pivoting mic.boom	348,49	415	422	401
	DT 297 PV MK II LTD 80 Ω NEW	Headset, 80 Ω, with condenser microphone (cardioid), for phantom power, without cable, with integrated limiter and pivoting mic. boom	328,99	392	398	378
	DT 297 PV MK II LTD 250 Ω NEW	Headset, 250 Ω, with condenser microphone (cardioid), for phantom power, without cable, with integrated limiter and pivoting mic. boom	328,99	392	398	378
	DT 790.00 MK II LTD 80 Ω NEW	Headset, 200/80 Ω, with dynamic microphone (hypercardioid), with cable 1,5 mtrs, open end, with integrated linmiter and pivoting mic. boom	341,18	406	413	392
	DT 797 PV MK II LTD 250 Ω NEW	Headset, 200/250 Ω, with condensor microphone (cardioid), with cable 1,5 mtrs, with 3-pin XLR connector and 6,35 stereo phone connector, with integrated limiter and pivoting mic. boom	365,55	435	442	420
		CABLES FOR DT 2XX SERIES HEADSETS				
15586	**K 190.00 - 1.5 m**	Connecting cable for DT 18*/19*/28*/29*-series with free ends (standard cable)	29,71	35	36	34
14311	**K 190.00 - 3.0 m**	Connecting cable for DT 18*/19*/28*/29*-series with free ends	32,78	39	40	38
15880	**K 190.26 - 1.5 m**	Connecting cable for DT 28*/29*-series with 4-pin mini-jack for SONY cameras (DR 100 compatible)	43,01	51	52	49
15591	**K 190.28 - 1.5 m**	Connecting cable for DT 18*/19*/28*/29*-series with 4-pin XLR female	48,13	57	58	55
15585	**K 190.39 - 1.5 m**	Connecting cable for DT 28*/29*-series - V.11 versions with 5-pin XLR male, for professional cameras	51,20	61	62	59
15593	**K 190.40 - 1.5 m**	Connecting cable for DT 18*/19*/28*/29*-series with 3-pin XLR male and 1/4" stereo jack	53,25	63	64	61
15633	**K 190.40 - 3.0 m**	Connecting cable for DT 18*/19*/28*/29*-series with 3-pin XLR male and 1/4" stereo jack	59,39	71	72	68
15590	**K 190.41 - 1.5 m**	Connecting cable for DT 18*/19*/28*/29*-series with 5-pin XLR male	51,20	61	62	59
	K 190.48 - 3.0 m	Connecting cable for DT 18*/19*/28*/29*-series with 2 x stereo mini-jack for multimedia applications	51,20	61	62	59
14802	**WK 190.00**	Coiled connecting cable for DT 18*/19*/28*/29*-series with free ends	59,39	71	72	68
		HEADZONE PRO SYSTEMS				
15594	**HEADZONE PRO V2.0**	Headzone Pro system consisting of; Headphones DT 880 Pro HT, rail HR 1.clip HC 1, basistation HBP 1 and H-bag	1.320,89	1.572	1.598	1.519
	HBP 1 V2.0	Basestation for Headzone (9,5"), 6 analoque inputs, IEEE 1394/FireWire interface, connection for headtracker, headphone output, incl. external powers supply, rack mount kit and desktop frame	1.013,71	1.206	1.227	1.166
15788	**HEADZONE PRO XT HT V2.0**	Headzone Pro XT HT system consisting of; Basestation Headzone PRO XT (19"), Headtracker HR 2, mounting clip HC 1, Firewirecable HVK-FW 6/6, Firewirecable HVK-FW 4/6, Software eand Powersupply	3.686,19	4.387	4.460	4.239
	HEADZONE PRO XT V2.0	Headzone XT system 5.1 Monitoring System without headtracking consisting of, Basestation Headzone Pro XT (19") Firewirecable HVK-FW 6/6, Firewirecable HVK-FW 4/6, Software eand Powersupply	3.327,81	3.960	4.027	3.827
15780	**DT 880 PRO HT**	Studioheadphone, 250 ohm, semi open, integrated ultra sonic transmitter for Headzone headtracker, single side coiled cable with streo mini-jack 1/4"adapter	358,38	426	434	412
15858	**DT 770 PRO HT**	Studioheadphone, 250 ohm, closed system, integrated ultra sonic transmitter for Headzone headtracker, single side coiled cable with streo mini-jack 1/4"adapter, comes in transport bag. Software (downloadable) needs to be implemented in base station HBP 1 before use !	276,47	329	335	318
	HR 1	Headzone headtracker (symetrical) receiver bracket for use with Headzone PRO with 2 ultrasonic receivers, connecting cable and stand adapter (3/8"), cable length2,0 mtrs (16,4 ft) - 4 pin mini-XLR	138,23	164	167	159
	HR 2 NEW	Headzone headtracker (symetrical) receiver bracket for use with Headzone PRO XT with 2 ultrasonic receivers, connecting cable and stand adapter (3/8"), cable length 5,0 mtrs (16,4 ft) - 5 pin XLR	307,18	366	372	353
	HC 1	Flexible clip to mount the Headzone rail HR 1 receiver bracket at	46,08	55	56	53

		HEADZONE ACCESSOIRES				
	HVK-FW 4/6-1,8M	Headzone FireWire/IEEE 1394 cable, 4 pin to 6 pin, length 1.8 mtr, max transfer rate 400Mbit/s	10,24	12	12	12
	HVK-FW 6/6	Headzone FireWire/IEEE 1394 cable, 6 pin to 6 pin, length 1.8 mtr, max transfer rate 400Mbit/s	10,24	12	12	12
	SUB-D25-XLR3-005 NEW	Headzone patch cable 25-pin SUB-D> 8 x XLR Female, cable length 0,5m (1,6ft)	127,99	152	155	147
	SUB-D25-XLR3-005 NEW	Headzone patch cable 25-pin SUB-D> 8 x XLR Female, cable length 5m (16ft)	153,60	183	186	177