



**ELECTRIC
SOUND**

premium brands & added value

Electric Sound Benelux B.V.

The Netherlands

Radioweg 5

1324 KW Almere (NL)

Tel. +31 (0)36 54 600 20

Fax. +31 (0)36 54 600 29

Belgium & Luxembourg

Weihoeck 3, Unit 5

1930 Zaventem (BE)

Tel. +32 (0)2 788 73 00

Fax. +32 (0)2 788 73 01

**KÖNIG & MEYER PRO SOUND & LIGHT
PRODUCTS**

LISTPRICING 19-04-2010

art.nr.	ARTICLE	DESCRIPTION	NEDERLAND BELGIE LUXEMBURG			
			EURO excl.BTW	EURO incl.19% BTW	EURO incl.21% BTW/TVA	EURO incl.15% BTW/TVA
<u>STANDS FOR INSTRUMENT AMP'S, MIXERS, MONITORS, 19" PANELS AND RACK'S</u>						
20159	28075	BLK Mixer stand, Heavy duty stand for amplifiers and mixers. Foldable. Spring-loaded locking bolt and locking screw. Felt-lined supporting brackets.	147,92	176	179	170
20214	28101	BLK Monitor stand, Perfect for amplifiers or monitor speakers. The support arms have a tilt angle of 42° and are height-adjustable. The stand is foldable for easy transport.	92,93	111	112	107
20498	28130	BLK Amp stand, Unique and solid amp stand. Holds up to 35 kg. Suitable for amplifiers, monitors and speakers. Easy to set up and fold. Stand is adjustable in width and tilt (3 tilt adjustment positions). Rubber-covered support arms. All one piece with no parts to lose. Comes with standard mic boom threads to attach K&M mic booms.	38,28	46	46	44
20191	28210	BLK Panel, Flat style, aluminum 2 mm thick, black.	6,52	8	8	7
20192	28220	BLK Panel, Flat style, aluminum 2 mm thick, black.	7,02	8	8	8
20193	28230	BLK Panel, Flat style, aluminum 2 mm thick, black.	11,03	13	13	13
20194	28240	BLK Panel, Flat style, aluminum 2 mm thick, black.	13,54	16	16	16
20206	28306	BLK Panel, For 6 XLR connectors. 1 space, black.	9,53	11	12	11
20207	28308	BLK Panel, For 8 XLR connectors. 1 space, black.	9,86	12	12	11
20208	28312	BLK Panel, For 12 XLR connectors. 1 space, black.	10,03	12	12	12
20161	28410	BLK Single rack rail, Steel, 10 spaces. Other space units upon request.	6,18	7	7	7
20217	28451	BLK Ventilation panel 1 HE with ventilation slots, black.	8,36	10	10	10
20301	28452	BLK Ventilation panel 2 HE with ventilation slots, black.	11,20	13	14	13
	28480	BLK Rackshelly, Two optional rackshellies suitable for rack shelves no. 28482 and 28483.	14,04	17	17	16
20164	28481	BLK Rack shelf, Easy-to-install 19" shelf for various components, black 300 mm	24,07	29	29	28
20647	28481	BLK Rack shelf, Easy-to-install 19" shelf for various components, black 380 mm	28,25	34	34	32
20165	28482	BLK Rack shelf, Easy-to-install 19" shelf for various components, black 300 mm	25,91	31	31	30
20467	28482	BLK Rack shelf, Easy-to-install 19" shelf for various components, black 380 mm	30,75	37	37	35
20166	28483	BLK Rack shelf, Easy-to-install 19" shelf for various components, black 300 mm	28,41	34	34	33
20477	28483	BLK Rack shelf, Easy-to-install 19" shelf for various components, black 380 mm	31,76	38	38	37
20315	28635	BLK Double rack rail steel, 35 spaces. Other space units upon request.	17,38	21	21	20
20356	28664	BLK 19"power box, 1 space Power Box, sturdy aluminum housing. Only for power current 16A 380 V~, with 5 pole CEE-plug and cable (length 2 m), 6 sockets 230 V~ in different colors on the front side. CE-mark.	118,34	141	143	136
20357	28665	BLK 19"power box, 1 space Power Box, sturdy aluminum housing. Only for alternating voltage. Power supply 16 A 230 V~. Plug with 2 m cable. With on/off switch on the front side and 7 sockets on the back side. CE-mark.	89,42	106	108	103
20358	28668	BLK 19"power box, 1 space Power Box, sturdy aluminum housing. Only for alternating voltage. Power supply 16 A 230 V~. New type of plug »power con« without cable, but with on/off switch on the front side and 6 sockets on the back side. CE-mark.	109,98	131	133	126
20359	28670	BLK 19"power box, 1 space Power Box, sturdy aluminum housing. Only for alternating voltage. Power supply 16 A 230 V~. Without on/off switch. With plug and 2 m cable and 8 sockets on the front side. CE-mark.	67,69	81	82	78
20360	28675	BLK 19"power box, 1 space Power Box, sturdy aluminum housing. Only for alternating voltage. Power supply 16 A 230 V~. With on/off switch, plug and 2 m cable and 7 sockets on the front side. CE-mark.	71,37	85	86	82
20361	28676	BLK 19"power box, 1 space Power Box, sturdy aluminum housing. Only for alternating voltage. Power supply 16 A 230 V~. With on/off switch and 6 sockets on the front side and 6 sockets on the back side. Plug and 2 m cable. CE-mark.	154,44	184	187	178
20291	40900	BLK Rack desk stand, 19" standard 8 unit-rack desk stand. Sturdy U-profile with steel rack rails. Comes with 16 cage nuts and screws.	78,39	93	95	90
20309	42015	BLK 19" rack, Inexpensive 19" standard 12 unit multi-rack stand, welded steel construction with 4 casters, 2 of them locking. Adjustable in tilt. Comes with steel rack rails and 16 cage nuts and screws.	107,81	128	130	124

20178	42020	BLK	19" rack wagon, Heavy-duty steel construction. Four casters, two lockable. Angle adjustable to 45° with spring-loaded locking mechanism. 12 space units in top section, 9 in lower section. Cage nuts incl. (32 pcs.). Rack shelves, drawers, blank and ventilation panels are available.	295,18	351	357	339
20179	42021	BLK	Extender brackets 19", for 42020. Provides additional 9 space units above rear of top section.	65,19	78	79	75
20500	42040	BLK	Mixer stand, Sturdy aluminium construction. Folds flat. Adjustable desk width. Non-skid rubber pads	108,65	129	131	125
20445	42080 #	BLK	DJ table, suspensor, The ultimate accessory for DJs! The practical DJ table by K&M includes 2 turntable positions and 1 mixer position. The aluminum top plates are on spring bearings, making it impossible for the unit to vibrate or shake. Records revolve evenly and performing is possible even on very shaky stages. Depending on the load on the table the suspension can be adjusted such that the turntables are suspended in a virtually floating manner. The table is adjustable in height and can be folded up for transport.	493,08	587	597	567
20687	44385		Price tag holder	8,86	11	11	10
20446	48240	BLK	Rack, Sturdy steel 19" rack with rack rails on the front and back side. 8 spaces. Appr. 430 mm deep.	152,44	181	184	175
20436	48240	BLK	Rack, Sturdy steel 19" rack with rack rails on the front and back side. 12 spaces. Appr. 430 mm deep.	185,87	221	225	214
20437	48260	BLK	Rack, Sturdy steel 19" rack with rack rails on the front and back side. Sloped front. 16 spaces. 425 mm deep at the top, H: 840 mm. At the bottom 561 mm deep. 4 casters are included.	291,50	347	353	335
20427	48260	BLK	Rack, Sturdy steel 19" rack with rack rails on the front and back side. Sloped front. 21 spaces. 390 mm deep at the top, H: 1070 mm. At the bottom 561 mm deep. 4 casters are included.	315,57	376	382	363
20502	48314	BLK	Multibay rack, Sturdy steel 19" Multi-Bay Rack type 5 with 14 spaces (H: 736 mm) with top and bottom. Durable textured black powder coat finish. Rack rails on the front and back side. Bottom with generous opening and laser cutting for cabling. Available options include side panel, rear and front doors. W: 553 mm D: 540 mm	311,56	371	377	358
20510	48321	BLK	Multibay rack, Sturdy steel 19" Multi-Bay Rack type 5 with 21 spaces (H: 1046 mm) with top and bottom. Durable textured black powder coat finish. Rack rails on the front and back side. Bottom with generous opening and laser cutting for cabling. Available options include side panel, rear and front doors. W: 553 mm D: 540 mm	328,28	391	397	378
20438	48329	BLK	Multibay rack, Sturdy steel 19" Multi-Bay Rack type 5 with 29 spaces (H: 1396 mm) with top and bottom. Durable textured black powder coat finish. Rack rails on the front and back side. Bottom with generous opening and laser cutting for cabling. Available options include side panel, rear and front doors. W: 553 mm D: 540 mm	367,72	438	445	423
20397	48337	BLK	Multibay rack, Sturdy steel 19" Multi-Bay Rack type 5 with 37 spaces (H: 1756 mm) with top and bottom. Durable textured black powder coat finish. Rack rails on the front and back side. Bottom with generous opening and laser cutting for cabling. Available options include side panel, rear and front doors. W: 553 mm D: 540 mm	406,83	484	492	468
	48343	BLK	Multibay rack, Sturdy steel 19" Multi-Bay Rack type 5 with 43 spaces (H: 2016 mm) with top and bottom. Durable textured black powder coat finish. Rack rails on the front and back side. Bottom with generous opening and laser cutting for cabling. Available options include side panel, rear and front doors. W: 553 mm D: 540 mm	423,88	504	513	487
20611	48362	BLK	Side panel, Sturdy steel side panel for 19" rack. Durable textured black powder coat finish. Easy to mount. Comes in pairs. Type SP5 with 14 space units.	227,65	271	275	262
20511	48363	BLK	Side panel, Sturdy steel side panel for 19" rack. Durable textured black powder coat finish. Easy to mount. Comes in pairs. Type SP5 with 21 space units.	261,42	311	316	301
20461	48364	BLK	Side panel, Sturdy steel side panel for 19" rack. Durable textured black powder coat finish. Easy to mount. Comes in pairs. Type SP5 with 29 space units.	295,01	351	357	339
20398	48365	BLK	Side panel, Sturdy steel side panel for 19" rack. Durable textured black powder coat finish. Easy to mount. Comes in pairs. Type SP5 with 37 space units.	328,28	391	397	378
	48366	BLK	Side panel, Sturdy steel side panel for 19" rack. Durable textured black powder coat finish. Easy to mount. Comes in pairs. Type SP5 with 43 space units.	412,52	491	499	474
	48372	BLK	Rear panel, Sturdy steel rear panel for 19" rack. Durable textured black powder coat finish. Type RAP with 14 space units.	123,19	147	149	142
	48373	BLK	Rear panel, Sturdy steel rear panel for 19" rack. Durable textured black powder coat finish. Type RAP with 21 space units.	141,91	169	172	163
20463	48374	BLK	Rear panel, Sturdy steel rear panel for 19" rack. Durable textured black powder coat finish. Type RAP with 29 space units.	156,95	187	190	180
20399	48375	BLK	Rear panel, Sturdy steel rear panel for 19" rack. Durable textured black powder coat finish. Type RAP with 37 space units.	184,86	220	224	213
	48376	BLK	Rear panel, Sturdy steel rear panel for 19" rack. Durable textured black powder coat finish. Type RAP with 43 space units.	194,06	231	235	223
	48382	BLK	Front door, Solid front door for 19" rack, with key and metal fittings. Durable textured black powder coat finish. Type DO-5 with 14 space units.	177,34	211	215	204
	48383	BLK	Front door, Solid front door for 19" rack, with key and metal fittings. Durable textured black powder coat finish. Type DO-5 with 21 space units.	199,74	238	242	230
	48384	BLK	Front door, Solid front door for 19" rack, with key and metal fittings. Durable textured black powder coat finish. Type DO-5 with 29 space units.	211,77	252	256	244
20400	48385	BLK	Front door, Solid front door for 19" rack, with key and metal fittings. Durable textured black powder coat finish. Type DO-5 with 37 space units.	251,89	300	305	290
	48386	BLK	Front door, Solid front door for 19" rack, with key and metal fittings. Durable textured black powder coat finish. Type DO-5 with 43 space units.	291,17	346	352	335
	48392		Plexi front door, Smoked plexi front door for 19" rack, with key and metal fittings. Type DOP-5 with 14 space units.	320,92	382	388	369

	48393		Plexi front door, Smoked plexi front door for 19" rack, with key and metal fittings. Type DOP-5 with 21 space units.	373,40	444	452	429
	48394		Plexi front door, Smoked plexi front door for 19" rack, with key and metal fittings. Type DOP-5 with 29 space units.	460,99	549	558	530
20411	48395		Plexi front door, Smoked plexi front door for 19" rack, with key and metal fittings. Type DOP-5 with 37 space units.	572,98	682	693	659
	48396		Plexi front door, Smoked plexi front door for 19" rack, with key and metal fittings. Type DOP-5 with 43 space units.	597,38	711	723	687
20401	48455	BLK	Casters, Set of 4 casters (2 locking) with mounting hardware.	36,94	44	45	42
20414	49010	BLK	Cable hanger, Steel wall mount cable hanger. For 14 cables. Side trays hold loose items.	28,92	34	35	33
20626	49035	BLK	Universal rack shelf, To mount half rack components, wireless units, and other gear horizontally. 1 space with several drillings for consumer equipment. door. 240 mm deep.	23,40	28	28	27
20456	49070	BLK	Sliding shelf, Sliding shelf. Heavy duty, all steel construction. Security lock for uncontrolled reverse motion. 1 space. 360 mm deep.	132,88	158	161	153
20459	49103	BLK	Rackmount lockbox, Lockbox storage unit, black, 3 spaces. Perfect for microphones, headphones etc. Keylock is standard.	88,75	106	107	102
	49104	BLK	Rackmount lockbox, Lockbox storage unit, black, 4 spaces. Perfect for microphones, headphones etc. Keylock is standard.	93,43	111	113	107
20363	49122	BLK	Rackmount storage, Utility drawer with keylock, 390 mm deep. Heavy-duty slides and steel construction. 2 spaces.	119,51	142	145	137
20348	49123	BLK	Rackmount storage, Utility drawer with keylock, 390 mm deep. Heavy-duty slides and steel construction. 3 spaces.	128,03	152	155	147
20501	49124	BLK	Rackmount storage, Utility drawer with keylock, 390 mm deep. Heavy-duty slides and steel construction. 4 spaces.	139,23	166	168	160
20460	49155	BLK	CD holder, CD Holder, for 26 CD's, 3 spaces, 150 mm deep. Partitioned to prevent the contents from tipping.	38,78	46	47	45
20428	49290	BLK	19" rack mounting lamp, Without dimmer. 1 lamp with long connector, power supply 230 V 50 Hz. 1 space.	85,08	101	103	98
20431	49302	BLK	Headphone holder, For 19" racks. Srew-mount. 2 spaces.	11,37	14	14	13
20531	49332		Plexiglass security cover, Incorporating a steel frame and a keylocked smoked-grey plexiglass door. 2 spaces.	53,15	63	64	61
20499	49334		Plexiglass security cover, Incorporating a steel frame and a keylocked smoked-grey plexiglass door. 4 spaces.	58,84	70	71	68
20371	49411	BLK	Panel, Steel panel, black, flanged style, 1.5 mm.	5,18	6	6	6
20372	49412	BLK	Panel, Steel panel, black, flanged style, 1.5 mm.	5,68	7	7	7
20373	49413	BLK	Panel, Steel panel, black, flanged style, 1.5 mm.	6,69	8	8	8
20374	49414	BLK	Panel, Steel panel, black, flanged style, 1.5 mm.	8,36	10	10	10
20417	49421	BLK	Panel, Aluminum panel, black, flanged style, 1.5 mm.	7,52	9	9	9
20418	49422	BLK	Panel, Aluminum panel, black, flanged style, 1.5 mm.	9,36	11	11	11
20419	49423	BLK	Panel, Aluminum panel, black, flanged style, 1.5 mm.	10,86	13	13	12
20458	49424	BLK	Panel, Aluminum panel, black, flanged style, 1.5 mm.	12,54	15	15	14
	49451	BLK	Panel, With integrated U-profile for Ela-installation. 2 spaces, black.	14,37	17	17	17
20454	49471	BLK	Ventilation panel, Perforated steel, flanged style, black. Large perforated pattern.	10,36	12	13	12
20455	49472	BLK	Ventilation panel, Perforated steel, flanged style, black. Large perforated pattern.	12,20	15	15	14
20425	49473	BLK	Ventilation panel, Perforated steel, flanged style, black. Large perforated pattern.	15,38	18	19	18
20421	49481	BLK	Ventilation panel, Perforated steel, flanged style, black. Tight perforated pattern.	14,54	17	18	17
20443	49482	BLK	Ventilation panel, Perforated steel, flanged style, black. Tight perforated pattern.	16,71	20	20	19
20683	49483	BLK	Ventilation panel, Perforated steel, flanged style, black. Tight perforated pattern.	20,56	24	25	24
			<u>MICROFOONSTATIEVEN & ACCESSOIRES</u>				
20040	199	BLK	Microphone stand, Extremely compact microphone stand. Three-piece shaft, non-marring height-adjustment system, lightweight plastic base with folding legs.	40,62	48	49	47
20154	260/1	NI	Microphone stand, Cast-iron round base, with anti-vibration rubber insert for noise filtration.	33,09	39	40	38
20155	260/1	BLK	Microphone stand, Cast-iron round base, with anti-vibration rubber insert for noise filtration.	28,93	34	35	33
20224	27105	NI	Microphone stand, Inexpensive stand with professional features. Fiberglass-reinforced plastic base with foldable legs. Complete with boom arm.	39,11	47	47	45
20158	27105	BLK	Microphone stand, Inexpensive stand with professional features. Fiberglass-reinforced plastic base with foldable legs. Complete with boom arm.	32,57	39	39	37
20495	27195	BLK	Microphone stand, Inexpensive stand with professional features. Fiberglass-reinforced plastic base with foldable legs. Complete with extendable boom arm.	41,79	50	51	48
20042	201/2	NI	Microphone stand, Folding, short-legged design with die-cast base. Noiseless height-adjustment.	38,78	46	47	45
20043	201/2	BLK	Microphone stand, Folding, short-legged design with die-cast base. Noiseless height-adjustment.	34,50	41	42	40
20045	201/A2	NI	Microphone stand, A world-wide classic. Folding, long-legged die-cast base for stability and ease of transport. Noiseless, non-scratching clutch-style height-adjustment mechanism.	39,78	47	48	46
20046	201/A2	BLK	Microphone stand, A world-wide classic. Folding, long-legged die-cast base for stability and ease of transport. Noiseless, non-scratching clutch-style height-adjustment mechanism.	36,00	43	44	41

20152	260	NI	Microphone stand, Heavy cast-iron round base, with anti-vibration rubber insert for noise filtration, plastic clutch-style height-adjustable system.	44,13	53	53	51
20153	260	BLK	Microphone stand, Heavy cast-iron round base, with anti-vibration rubber insert for noise filtration, plastic clutch-style height-adjustable system.	39,64	47	48	46
20508	26025	BLK	Microphone stand, Attractive microphone stand in a slim design for stage and studio. Cast-iron round base with an anti-vibration rubber ring for noise filtration. Ergonomically designed clutch for an easy adjustment of the height.	47,47	56	57	55
20701	26150	BLK	Elegant high-class microphone stand, rod combination completely chrome-plated. Round glass base with anti-vibration rubber bumps for noise filtration. Height adjustable with chrome-plated clutch.	84,74	101	103	97
20473	25680	BLK	One hand microphone stand, With the unique »Soft-Touch« one-hand clutch the height can be adjusted with a quick squeeze to easily raise and lower the mic. Metal base with foldable legs for compact transport. Quality black powder coating is extremely durable.	55,83	66	68	64
20650	26045	BLK	This model has a round, heavy cast-base with a cut-out design that allows for stacking of up to 5 microphone stands.	37,94	45	46	44
20474	26085	BLK	One hand microphone stand, With the unique »Soft-Touch« one-hand clutch the height can be adjusted with a quick squeeze to easily raise and lower the mic. Cast iron round base. Quality black powder coating is extremely durable.	53,82	64	65	62
20050	210/2	NI	Microphone stand, The industry standard for a mic stand and boom arm combination. Package consists of the 201A/2 microphone stand and the 211 boom arm. Folding base for ease of transport. Long legs for added stability. The 210/2 - a classic for 30 years. More than 2 million sold.	54,32	65	66	62
20051	210/2	BLK	Microphone stand, The industry standard for a mic stand and boom arm combination. Package consists of the 201A/2 microphone stand and the 211 boom arm. Folding base for ease of transport. Long legs for added stability. The 210/2 - a classic for 30 years. More than 2 million sold.	47,14	56	57	54
20293	210/4	NI	Microphone stand, A more compact version of the classic 210/2. The combination of the short-legged 201/2 mic stand and the 211/1 telescopic boom arm. Like the 210/9, the 210/4 sets the standard for professional microphone boom stands.	56,50	67	68	65
20294	210/4	BLK	Microphone stand, A more compact version of the classic 210/2. The combination of the short-legged 201/2 mic stand and the 211/1 telescopic boom arm. Like the 210/9, the 210/4 sets the standard for professional microphone boom stands.	51,22	61	62	59
20054	210/9	NI	Microphone stand, A more compact version of the classic 210/2. The combination of the long-legged 201A/2 mic stand and the 211/1 telescopic boom arm. Like the 210/2, the 210/9 sets the standard for professional microphone boom stands.	52,07	62	63	60
20055	210/9	BLK	Microphone stand, A more compact version of the classic 210/2. The combination of the long-legged 201A/2 mic stand and the 211/1 telescopic boom arm. Like the 210/2, the 210/9 sets the standard for professional microphone boom stands.	51,43	61	62	59
20225	210/6	NI	Microphone stand, Modern update of the classic 210/2. Zinc die-cast base with long folding legs. Special height-adjustment mechanism.	46,47	55	56	53
20226	210/6	BLK	Microphone stand, Modern update of the classic 210/2. Zinc die-cast base with long folding legs. Special height-adjustment mechanism.	41,36	49	50	48
20599	21070	BLK	Low-priced all-metal-stand. Consists of tubing assembly, boom arm and zinc die-cast base with long folding legs. Square swivel joint with large wing nut.	39,45	47	48	45
20402	210/6	GR	Microphone stand "soft touch, Consists of tubing assembly, boom arm and zinc die-cast base with long folding legs. Square swivel joint with large wing nut. Attractive gray Soft-Touch powder coating.	49,31	59	60	57
20227	210/8	NI	Microphone stand, Consists of tubing assembly and extendable boom arm. Zinc die-cast base with long folding legs. Square swivel joint with large wing nut.	51,15	61	62	59
20228	210/8	BLK	Microphone stand, Consists of tubing assembly and extendable boom arm. Zinc die-cast base with long folding legs. Square swivel joint with large wing nut.	44,57	53	54	51
20506	210/8	GR	Microphone stand "soft touch, Like model 21060, but with extendable boom arm.	53,82	64	65	62
20189	200 #	NI	Microphone stand, Specially designed folding die-cast base with built-in anti-vibration filters in legs. Stand isolates microphone from vibrations. Well suited for recording studios.	64,69	77	78	74
20041	200	BLK	Microphone stand, Specially designed folding die-cast base with built-in anti-vibration filters in legs. Stand isolates microphone from vibrations. Well suited for recording studios.	62,36	74	75	72
20053	21021	BLK	Overhead microphone stand, Especially designed for studios and drummers. Taller and longer than most stands. Long legs fold for compact storage and easy transport.	77,22	92	93	89
20349	25600	BLK	Microphone stand, High-quality microphone stand with telescopic boom arm. Die-cast base with folding legs. Unique design retains all screws and levers without tension. Patented clamping lever can be fixed in any position for holding mic cable, etc.	82,07	98	99	94

20707	20800 NEW 2009	BLK	This compact overhead microphone stand is now even lighter and more stable. Thanks to a new leg combination and a new clamping element, its weight has been reduced to 3.6 kg. The leg base diameter of 1 m affords stability and safety. A range of different boom arms can be attached using the 3/8" thread adaptor. The stand extends to a height of over 3 m.	84,41	100	102	97
20686	20811 NEW 2009	BLK	A microphone stand in a two-piece folding design that extends to over 4 m and as such is very suitable for organ and choir recordings. There is an extra safety ring lock for stability. The extension tube has a 1/2" thread connector. The stand can optionally be combined with boom arm 21231.	203,58	242	246	234
20230	21411	BLK	Microphone stand, Extremely sturdy overhead mic stand for studio and broadcast applications. Extendible up to 2 m. Locking height-adjustment mechanism for added safety. 1/2" thread for use with 21231 boom arm. Collapsible design for easy transport and storage.	98,78	118	120	114
20602	21430	BLK	Mobile heavy steel microphone stand for studio or stage. 10 kg cast metal base, low centre of gravity for high level safety with 3 lockable castor wheels. Rod combination extends to over 2 m with additional locking mechanism. Extendable boom arm with a 3 kg counterweight and 5/8" connecting thread. Additional mini boom arm with 5/8"- and 3/8"- connecting thread, fully adjustable regardless of the position of the main boom arm. e.g. to use with studio microphones.	257,74	307	312	296
20229	21231 #	BLK	Boom arm, Telescopic boom arm with 3/8" thread. Adjustable counterweight. For use with model 20811 and 21411.	100,12	119	121	115
20143	252 #	NI	Microphone stand, Three-piece telescoping shaft. Metal, non-marring height-adjustment mechanisms, complete with boom arm.	67,69	81	82	78
20144	252	BLK	Microphone stand, Three-piece telescoping shaft. Metal, non-marring height-adjustment mechanisms, complete with boom arm.	65,35	78	79	75
20505	254	BLK	Microphone stand including boom (very simple model)	22,93	27	28	26
20145	255 #	CHR	Microphone stand, Low-level stand with folding base, complete with long, 2-piece extendable boom arm.	69,53	83	84	80
20146	255	BLK	Microphone stand, Low-level stand with folding base, complete with long, 2-piece extendable boom arm.	64,85	77	78	75
20150	259/1 #	CHR	Microphone stand, Extra low design for bass drums or special use. Die-cast base with folding legs. Comes complete with boom arm.	47,97	57	58	55
20151	259/1	BLK	Microphone stand, Extra low design for bass drums or special use. Die-cast base with folding legs. Comes complete with boom arm.	46,13	55	56	53
20341	25950	BLK	Microphone stand "rien", Extra low design for bass drums or special use. Very short and heavy legs provide maximum stability. Legs are foldable for easy transport. Comes with two-piece boom arm 21140.t	50,31	60	61	58
20148	259	NI	Microphone stand, Low-level, telescopic stand with foldable legs. Comes with 2-piece boom arm.	57,50	68	70	66
20149	259	BLK	Microphone stand, Low-level, telescopic stand with foldable legs. Comes with 2-piece boom arm.	52,50	62	64	60
20526	259	GR	Microphone stand "soft touch", Low-level, telescopic stand with foldable legs. Comes with 2-piece boom arm. Attractive gray Soft-Touch powder coating.	60,34	72	73	69
20219	25960	BLK	Microphone stand, Low profile round-base mic stand with telescopic boom arm, designed for bass drums and acoustic instruments. Heavy cast-iron round base, with anti-vibration rubber insert for noise filtration.	55,83	66	68	64
20406	25910	GR	Microphone stand "soft touch", Extra low design for bass drums or special use. Comes complete with boom arm. Attractive gray Soft-Touch powder coating.	48,64	58	59	56
20056	211	NI	Boom arm, Classic one-piece boom arm with 3/8" thread, and sliding adjustment through non-scratching swivel joint. Easy tightening with T-bar locking screw. Complete with locking washer and plastic handgrip.	19,22	23	23	22
20057	211	BLK	Boom arm, Classic one-piece boom arm with 3/8" thread, and sliding adjustment through non-scratching swivel joint. Easy tightening with T-bar locking screw. Complete with locking washer and plastic handgrip.	18,89	22	23	22
20058	211/1	NI	Boom arm, Classic two-piece telescopic boom arm with 3/8" thread. Silent, scratchless swivel joint for adjustment of angle, easy tightening with T-bar locking screw.	21,90	26	26	25
20059	211/1	BLK	Boom arm, Classic two-piece telescopic boom arm with 3/8" thread. Silent, scratchless swivel joint for adjustment of angle, easy tightening with T-bar locking screw.	20,57	24	25	24
20541	21105	BLK	Counter weight, Used for heavy microphones. Fits all one-piece K&M boom arms with 3/8" thread connector or tube diameter 15 mm. Easy mounting.	15,88	19	19	18
20316	21140	BLK	Boom arm, Two-piece telescopic boom arm with 3/8" thread. Complete with locking washer and plastic grip. Smooth, silent and scratch-free adjustment thanks to large wing nut.	19,05	23	23	22
20281	21160	BLK	Boom arm, Short one-piece boom arm with 3/8" thread. Locking washer and plastic grip. Smooth adjustment. Easy to tighten with wing nut.	14,21	17	17	16
20342	23105	BLK	Table microphone stand, Inexpensive, handy table microphone stand for professional use. Sturdy plastic base with collapsible light-weight plastic legs and 3/8" thread.	9,36	11	11	11
20106	231/1	NI	Table microphone stand, Small, lightweight stand, plastic base with folding legs, 3/8" thread.	6,85	8	8	8

20716	23150	ZW	The telescopic microphone stand with a 1/4" threaded connector is extremely versatile. Its height can be adjusted from 230 to 400 mm using the practical clamping lever. This light-weight three-legged stand with folding legs is suitable for mobile operation. The robust foot end caps provide stability and reduce undesirable transmission noise.	23,65	28	29	27
20108	232	NI	Table microphone stand, Sound-absorbing cast-iron base with nickel-plated or black powder-coated screw-in rod, 3/8" thread.	23,73	28	29	27
20109	232	BLK	Table microphone stand, Sound-absorbing cast-iron base with nickel-plated or black powder-coated screw-in rod, 3/8" thread.	23,40	28	28	27
20322	23220	BLK	Table microphone stand, Sound absorbing cast-iron base with 3/8" thread.	21,39	25	26	25
20355	23262	GR	Table microphone stand, Unique and small table mic stand with ball-shaped base. With anti-vibration felt insert for noise filtration. 3/8" thread.	21,39	25	26	25
20468	23266	GR	Table microphone stand, Unique and small table mic stand with compact base. With anti-vibration felt insert for noise filtration. 3/8" thread.	21,39	25	26	25
20603	23280	BLK	Small, tabletop microphone stand, round glass base. Anti-vibration rubber bumps for noise filtration. Stainless steel threaded bolt.	45,97	55	56	53
20112	233	NI	Table/floor mic stand, Combination floor and table stand. Heavy black cast-iron base with sound absorbing rubber insert. Height-adjustable 2-piece tubing.	36,77	44	44	42
20113	233	BLK	Table/floor mic stand, Combination floor and table stand. Heavy black cast-iron base with sound absorbing rubber insert. Height-adjustable 2-piece tubing.	36,27	43	44	42
20529	233	GR	Table/floor mic stand, Combination floor and table stand. Heavy black cast-iron base with sound absorbing rubber insert. Height-adjustable 2-piece tubing.	35,36	42	43	41
20175	29390	BLK	Microphone table base, Black cast-iron base with a horizontally mounted XLR-style female socket on upper face. Removable plate, suitable for fitting switches, indicators, controls or connectors, with access to space for additional circuitry. Base is fitted with rear-mounted 3-pole XLR male connector.	85,08	101	103	98
20114	234 #	NI	Table/floor mic. Stand, Black rectangular cast-iron base with tilt angle adjustment, 2-piece adjustable extension tubing with non-marring height-adjustment mechanism. Ideal for drums and studios.	48,31	57	58	56
20115	234	BLK	Table/floor mic stand, Black rectangular cast-iron base with tilt angle adjustment, 2-piece adjustable extension tubing with non-marring height-adjustment mechanism. Ideal for drums and studios.	49,31	59	60	57
20480	29373	BLK	Microphone table base, A beautifully designed, compact, zinc die-cast base. 5-pin XLR-style male connector (on the mixing console side) and 3-pin XLR-style female connector (on the microphone side), completely mounted, crackle-free switching, with phantom powering-pilot light, with switch (gray). Two diodes indicate the operating state (voltage / microphone ON/OFF).	111,32	132	135	128
20481	29374	BLK	Microphone table base, A beautifully designed, compact, zinc die-cast base. 5-pin XLR-style male connector (on the mixing console side) and 3-pin XLR-style female connector (on the microphone side), completely mounted, crackle-free switching, with phantom powering-pilot light, with pushbutton (black). Two diodes indicate the operating state (voltage / microphone ON/OFF).	111,32	132	135	128
20482	29375	BLK	Microphone table base, Beautifully designed, compact, zinc die-cast base. 3-pin XLR connections (male/female), completely mounted, crackle-free switching, with phantom powering-pilot light, with switch (gray). Two diodes indicate the operating state (voltage / microphone ON/OFF).	111,32	132	135	128
20483	29376	BLK	Microphone table base, Beautifully designed, compact, zinc die-cast base. 3-pin XLR connections (male/female), completely mounted, without pushbutton or switch.	73,04	87	88	84
20484	29377	BLK	Microphone table base, Beautifully designed, compact, zinc die-cast base. 3-pin XLR connections (male/female), completely mounted, crackle-free switching, with phantom powering-pilot light, with pushbutton (black). Two diodes indicate the operating state (voltage / microphone ON/OFF).	111,32	132	135	128
20485	29378	BLK	Microphone table base, Beautifully designed, compact, zinc die-cast base. 5-pin XLR connections (male/female), completely mounted, without pushbutton or switch.	73,04	87	88	84
20176	29394	BLK	Microphone table base, Similar to 29390, but with fitted LED illuminated single pole changeover switch and 3-pole XLR-style female connector. Mounted on the removable plate. A 5 pole XLR-style male connector on the rear.	87,42	104	106	101
20448	29397 #	BLK	Microphone table base, with gooseneck 300 mm	174,33	207	211	200
20080	215	NI	Thread adapter, 1/2" and 3/8" female thread, 5/8" 27 gauge male thread.	1,59	2	2	2
20081	216	NI	Thread adapter, 5/8" 27 gauge female thread, 3/8" male thread.	2,42	3	3	3
20082	217	NI	Thread adapter, 3/8" female thread, 5/8" 27 gauge male thread.	1,09	1	1	1
20083	218	NI	Thread adapter, 1/2" female thread, 3/8" male thread.	2,09	2	3	2
20084	219	NI	Thread adapter, 3/8" female thread, 1/2" male thread.	2,26	3	3	3

20117	23510	ZW	The flexible microphone bar for microphone stands. Two moveable bars position the microphone where ever you would like it. Each bar is fitted with a captive knurled screw. The entire bar can be screwed onto all standard microphone stands	14,21	17	17	16
20340	23550	BLK	Microphone bar, Connects to top of mic stands for holding 2 microphones or boom arms. 3/8" locking screws, adjustable from 60 to 172 mm.	10,36	12	13	12
20118	236	BLK	Microphone bar, Connects to top of mic stands for holding 4 microphones or boom arms. 3/8" locking screws.	20,06	24	24	23
20093	223	NI	Gooseneck, 3/8" female and male thread. L: 400 mm, diameter: 15 mm.	21,73	26	26	25
20094	223	BLK	Gooseneck, 3/8" female and male thread. L: 400 mm, diameter: 15 mm.	22,90	27	28	26
20095	224	NI	Gooseneck, 3/8" female and male thread. L: 300 mm, diameter: 15 mm.	17,38	21	21	20
20096	224	BLK	Gooseneck, 3/8" female and male thread. L: 300 mm, diameter: 15 mm.	17,38	21	21	20
20097	225	NI	Gooseneck, 3/8" female and male thread. L: 200 mm, diameter: 15 mm.	14,04	17	17	16
20098	225	BLK	Gooseneck, 3/8" female and male thread. L: 200 mm, diameter: 15 mm.	14,04	17	17	16
20099	226	NI	Gooseneck, 3/8" female and male thread. L: 200 mm, diameter: 11 mm.	10,86	13	13	12
20222	226	BLK	Gooseneck, 3/8" female and male thread. L: 200 mm, diameter: 11 mm.	10,86	13	13	12
20100	227	NI	Gooseneck, 3/8" female and male thread. L: 500 mm, diameter: 18.5 mm.	50,14	60	61	58
20101	227	BLK	Gooseneck, 3/8" female and male thread. L: 500 mm, diameter: 18.5 mm.	56,66	67	69	65
20102	228	NI	Gooseneck, 3/8" female and male thread. L: 600 mm, Diameter: 18.5 mm.	59,84	71	72	69
20103	228	BLK	Gooseneck, 3/8" female and male thread. L: 600 mm, Diameter: 18.5 mm.	63,01	75	76	72
20104	230/1	NI	Gooseneck, 3/8" female threading with lateral cable entry terminating in a 3 pole bushing with NC3FX XLR spring bushing. L: 300 mm, diameter: 15 mm.	37,78	45	46	43
20254	230/1	BLK	Gooseneck, 3/8" female threading with lateral cable entry terminating in a 3 pole bushing with NC3FX XLR spring bushing. L: 300 mm, diameter: 15 mm.	36,77	44	44	42
20105	230/2	NI	Gooseneck, 3 pole plug NC3MX XLR terminating in a 3 pole bushing with NC3FX XLR spring bushing. L: 300 mm, diameter: 15 mm.	38,78	46	47	45
20246	230/2	BLK	Gooseneck, 3 pole plug NC3MX XLR terminating in a 3 pole bushing with NC3FX XLR spring bushing. L: 300 mm, diameter: 15 mm.	37,61	45	46	43
	230/3	NI	Gooseneck, 3/8" female threading with lateral cable entry terminating in a 3 pole bushing with NC3FX XLR spring bushing. L: 400 mm, diameter: 15 mm.	42,29	50	51	49
20321	230/3	BLK	Gooseneck, 3/8" female threading with lateral cable entry terminating in a 3 pole bushing with NC3FX XLR spring bushing. L: 400 mm, diameter: 15 mm.	41,29	49	50	47
	230/4	NI	Gooseneck, 3 pole plug NC3MX XLR terminating in a 3 pole bushing with NC3FX XLR spring bushing. L: 400 mm, diameter: 15 mm.	40,78	49	49	47
20299	230/4	BLK	Gooseneck, 3 pole plug NC3MX XLR terminating in a 3 pole bushing with NC3FX XLR spring bushing. L: 400 mm, diameter: 15 mm.	39,45	47	48	45
20121	23750	BLK	Microphone "fishing pole", Lightweight, adjustable 2-piece aluminum tube used for remote positioning of microphones for recording and broadcasting. Rough textured hand-grips and secure locking rings. Handy carrying case included.	60,17	72	73	69
20122	23760	BLK	Microphone "fishing pole", Same as 23750, but with 3-piece tubing.	96,94	115	117	111
20594	23770	BLK	Microphone "fishing pole", Lightweight, 4-piece glass fibre rod combination, extra long. Supports 0.5 kg. Microphone cable can be routed through the tubing. Padded, anti-slip grip section. Folds compactly into a practical carrying case.	107,31	128	130	123
20119	237	NI	Table clamp, 3/8" threaded bolt. For goosenecks, etc.	8,86	11	11	10
20120	237	BLK	Table clamp, 3/8" threaded bolt. For goosenecks, etc.	8,52	10	10	10
20123	238 #	NI	Microphone holder, Attaches to stands with diameter up to 23 mm. 3/8" threaded bolt for attaching goosenecks and mic clips.	13,54	16	16	16
20335	238	BLK	Microphone holder, Attaches to stands with diameter up to 23 mm. 3/8" threaded bolt for attaching goosenecks and mic clips.	13,87	17	17	16
20343	23850	BLK	Microphone desk arm, Easy running microphone desk arm with 3/8" or 5/8" thread for studios and multi-media workstations; black powder-coated. Easy to handle. The microphone arm keeps the position which you select. The included screw-on clamp (adjust-able up to 55 mm) or the additional available table flange offer a multi-purpose use. Max. load capacity 0.8 kg. 5 m microphone cable (3-pole XLR connection) is included.	87,43	104	106	101
20344	23855	BLK	Table flange, Suitable for microphone arm 23850.	14,88	18	18	17

20125	240 #	BLK	Microphone holder for drums.	29,92	36	36	34
20126	240/1	BLK	Microphone arm, Attaches to stands with diameter from 15 to 22 mm. With prismatic clamp connector. Comes complete with adjustable and swiveling boom arm with 3/8" thread.	29,08	35	35	33
20469	24030	NI	Microphone holder for drums, Unique, compact holder to attach microphones to drums. Easy to mount and remove. Rubber inserts absorb noise and shock. No parts to lose. Tightens securely. With 3/8" thread.	14,21	17	17	16
20379	24030	BLK	Microphone holder for drums, Unique, compact holder to attach microphones to drums. Easy to mount and remove. Rubber inserts absorb noise and shock. No parts to lose. Tightens securely. With 3/8" thread.	14,04	17	17	16
20545	24035	BLK	Microphone holder for drums, Compact holder to attach microphones to drums, esp. bass drums. The microphone can be slid up to 70 mm on the mounting rail and placed very near to the drum. Easy mounting, no parts to lose. Rubber washer and inserts absorb noise and shock, "R.I.M.S" suitable. With 3/8" thread.	15,04	18	18	17
20648	24035	NI	Microphone holder for drums, Compact holder to attach microphones to drums, esp. bass drums. The microphone can be slid up to 70 mm on the mounting rail and placed very near to the drum. Easy mounting, no parts to lose. Rubber washer and inserts absorb noise and shock, "R.I.M.S" suitable. With 3/8" thread.	14,88	18	18	17
20127	240/5	BLK	Microphone holder, Fully adjustable to any angle, holds microphones or boom arms with 3/8" threaded bolt. Attaches to round or flat surfaces.	28,25	34	34	32
20147	258	BLK	Table microphone clamp, Extendible steel tubing. Clamping mechanism allows tube to swivel full 360 degrees.	41,45	49	50	48
20595	85035	BLK	Microphone clip, Tapered slip-in microphone clip, diameter approx. 17 mm, high quality elastic rubber. 3/8 and 5/8"	1,82	2	2	2
20690	85040	BLK	Thread adapter, Plastic material, 3/8" female thread, 5/8" 27 gauge male thread.	0,84	1	1	1
20231	85050	BLK	Microphone clip, Tapered slip-in microphone clip diameter approx. 22 mm, elastic rubber material.	1,82	2	2	2
20270	85055	BLK	Microphone clip, Tapered slip-in microphone clip diameter approx. 28 mm, elastic rubber material.	1,93	2	2	2
20382	85060	BLK	Microphone clip, Tapered slip-in microphone clip diameter approx. 34 mm, elastic rubber material.	2,04	2	2	2
20085	221a	BLK	Table flange, Black base and tube with 3/8" thread.	16,71	20	20	19
20088	221c	BLK	Table flange, With 3/8" hexagonal screw for vertical and lateral connection of goosenecks, etc. 4 mm cable entry hole.	15,21	18	18	17
20089	221d	BLK	Table flange, Black flange with 3/8" hexagonal screw to connect goosenecks etc. 4 mm cable entry hole.	6,52	8	8	7
20086	221/6 #	BLK	Microphone stand, ceiling mounting	35,10	42	42	40
20664	23860 NEW	BLK	This is a new microphone arm in a modern design for fast and flexible microphone positioning in studios or multimedia workplaces. The internal microphone cable with a 3 pin XLR connection is 6 m long. The aluminium table clamp can be attached to a table top depth of max. 55 mm. Microphones to max. weight of 1.5 kg can be freely positioned. The microphone arm can optionally be fixed with the additionally obtainable table flange 23855	157,12	187	190	181
20124	23956	BLK	Pop killer, The K&M Popkiller - a world-wide classic. For stands with diameter of up to 23 mm. Double nylon screen for superior performance. Unobtrusive black round filter frame. Non-marring locking screw prevents scratching of mic stand.	21,21	25	26	24
20444	23966	BLK	Pop killer, The large Popkiller for modern studio engineering. The large 200 mm nylon screen guarantees optimum sound filtering during studio recording. The Popkiller with flexible gooseneck can be screwed to all standard microphone stands (rod diameter max. 23 mm).	30,09	36	36	35
			<u>STANDS FOR LOUDSPEAKERS, MONITORS AND LIGHTING EQUIPMENT AND ACCESSORIES</u>				
20031	19581 #		Mounting plate wood, incl. anti-slippery surface for TV-monitors without flange 195/8	53,36	63	65	61
20533	21402		Warning strip, No more tripping: reflective collar of heavy duty nylon fabric for better safety especially in poor lighting conditions. Yellow/black stripes printed with "CAUTION". Attaches to base of the stand with Velcro.	10,20	12	12	12
20668	21435 NEW MODEL 2009	BLK	The standard speaker stand constructed from steel tubing has been significantly improved. The new legs with a tubing diameter of 35 mm and the large, fixed foot end caps guarantee stability and safety. Lasered bore holes and durable, robust plastic saddle washers improve the coefficient of friction between the legs and braces and prevent scratching of the finish. A compact clamp with a patented push-button system affords user-friendly stand height adjustment. The locking screw provides additional stability and vibration-free speaker mount. Additional features include a pull-out guard for the extension tube and an integral anti-shock component.	54,64	65	66	63

20681	21436 NEW MODEL 2009	BLK	The standard speaker stand constructed from aluminum has been significantly improved. The new legs with a tubing diameter of 35 mm and the large, fixed foot end caps guarantee stability and safety. Lasered bore holes and durable, robust plastic saddle washers improve the coefficient of friction between the legs and braces, and prevent scratching of the finish. A compact clamp with a patented push-button system affords user-friendly stand height adjustment. The locking screw provides additional stability and vibration-free speaker mount. Additional features include a pull-out guard for the extension tube and an integral anti-shock component.	61,07	73	74	70
	21437 NEW MODEL 2009	BLK	Steel speaker stand. Height adjustment with locking screw and additional safety pin. A unique patented mandrel on the extension tube automatically straddles when the speaker is mounted and provides a firm fit for the speaker.	77,89	93	94	90
20551	21438	BLK	Speaker stand, A light-weight speaker stand with U-profile leg construction in aluminum, extension tube in steel. Height adjustment is made with a locking screw and additional safety pin. A unique patented mandrel on the extension tube automatically straddles when the speaker is mounted and provides a firm fit for the speaker.	84,74	101	103	97
	21438 NEW MODEL 2009	BLK	A light-weight aluminum speaker stand, extension tube in steel. Height adjustment is made with a locking screw and additional safety pin. A unique patented mandrel on the extension tube automatically straddles when the speaker is mounted and provides a firm fit for the speaker.	84,74	101	103	97
20077	21420	BLK	Speaker/monitor stand, Lightweight aluminum stand for loads up to 12 kg. Ideal for small speakers and monitors. Extension tube diameter 25 mm. Gradually height-adjustable. Non-scratching locking screw. Foldable and light weight for easy transport. Optional carrying case 21422, adapter 19680 and flange adapter 19665 available.	42,96	51	52	49
20037	19665	BLK	Flange adapter, Suitable for 21420 or stands with tubing diameter of 25 mm. Designed to be inserted and screwed onto speaker enclosures. Plastic-coated steel flange, diameter 105 mm, depth 78 mm.	18,22	22	22	21
20039	19680	BLK	Universal adapter, For stands 21420 with tubing diameter of 25 mm. Attaches to speakers and monitors. Secured by handknob. The connection plate/angle is provided with slots to fit all conventional speaker and monitor systems.	29,92	36	36	34
20212	21421		Carrying case, Designed to carry 2 K&M microphone stands. Made of waterproof nylon. Black with screenprinted logo. Two inside compartments with zipper and sturdy handles.	15,04	18	18	17
20504	21422		Carrying case, Designed to carry 2 K&M speaker/monitor stands 21420. Made of black waterproof nylon. Two inside compartments with draw-string closure and sturdy handles.	15,04	18	18	17
20717	21431	ZW	The short moveable microphone boom arm is suitable for many applications. It is particularly appropriate for overhead uses. There are 3/8" and 5/8" threaded connectors to take the microphone holder. Thanks to the flexible clamping, the boom arm can be positioned in length and angle with one simple movement.	15,88	19	19	18
20680	21434 NEW MODEL 2009	BLK	This new steep-angled mounting aid is designed to simplify attachment of loud speakers to stands. The robust peg also reduces vibration transfer from speaker to stand. The new design fits all stands with a tubing diameter of 35 mm.	3,18	4	4	4
20596	21440 #	BLK	Speaker stand "ring lock", Aluminum speaker stand, extension tube made from steel fitted with a unique patented expanding mandrel system which provides a tight and firm fit for the speaker. The moveable plastic splints separate the speaker from the stand creating a vibration-free connection. Easy to use ring lock. Height adjustment using a non-scratching locking screw and additional safety pin for a secure hold.	109,50	130	132	126
	21440 NEW MODEL 2009	BLK	Aluminum speaker stand, extension tube made from steel fitted with a unique patented expanding mandrel system which provides a tight and firm fit for the speaker. The moveable plastic splints separate the speaker from the stand creating a vibration-free connection. Easy to use ring lock. Height adjustment using a non-scratching locking screw and additional safety pin for a secure hold.	109,50	130	132	126
20597	21441	BLK	Adapter sleeve "ring lock", Steel adapter sleeve attaches to speaker stands with tubing diameter of 35 mm, mounts with a locking screw. Integrated unique patented expanding mandrel system which provides a tight and firm fit for the speaker. The moveable plastic splints separate the speaker from the stand creating a vibration-free connection.	40,72	48	49	47
20486	21450		Speaker stand, An easy-to-carry speaker stand made of high quality aluminum. Fiberglass-reinforced fittings and an additional safety pin ensure stable support for the speakers. The height and feet adjust by an easy-to-use clamping lever.	46,07	55	56	53
20079	21455 #	BLK	Speaker stand, Aluminum speaker stand especially designed for low to medium height applications. Extension tube diameter 35 mm. Height-adjustable by a spring-loaded locking screw and safety bolt.	110,65	132	134	127
	21455 NEW MODEL 2009	BLK	Aluminum speaker stand especially designed for low to medium height applications. Extension tube diameter 35 mm. Height-adjustable by a spring-loaded locking screw and safety bolt.	110,65	132	134	127
20451	21485 #	BLK	Speaker stand, An absolute hit in price/performance and versatility! This 3-leg aluminum speaker stand weighs a mere 3.3 kg. A handy snap closure system makes the stand easy to adjust to 5 different heights. An additional clamp screw ensures that the speaker is held securely in place without vibrating. A special tube lock prevents that the extension tube is pulled out accidentally from the main tube.	110,65	132	134	127
20407	21494	BLK	Speaker stand, The new 5-leg construction of U-profile tubing is a crucial step towards a higher stability of the stand. The height adjustment mechanism features a comfortable push button system which locks the extension tube in 5 different positions. The additional locking screw ensures a stationary, vibration-free mount for speakers. A special tube lock prevents the extension tube from pulling out accidentally. The lightweight stand is constructed from first-class aluminum tubing with a durable black finish and weighs only 2.2 kg.	107,81	128	130	124

20062	213/1	BLK	Safety ring, Safety accessory for all extension tubes with diameter of 36 mm.	18,72	22	23	22
20685	214/6 NEW MODEL 2009	BLK	The world-wide acclaimed speaker stand has been upgraded. All clamps are now high quality zinc die-cast. The new leg construction and large fixed foot end caps enhance safety and stability even further. This professional stand is TÜV (German Technical Supervisory Agency) approved for a maximum central load capacity of 50 kg. Other features such as the pull-out guard for the extension tube, the integral anti-shock component and comfortable height adjustment with spring-loaded bolt and locking screw have of course been retained.	94,07	112	114	108
	214/6 NEW MODEL 2009	ALU	The world-wide acclaimed speaker stand has been upgraded. All clamps are now high quality zinc die-cast. The new leg construction and large fixed foot end caps enhance safety and stability even further. This professional stand is TÜV (German Technical Supervisory Agency) approved for a maximum central load capacity of 50 kg. Other features such as the pull-out guard for the extension tube, the integral anti-shock component and comfortable height adjustment with spring-loaded bolt and locking screw have of course been retained.	121,18	144	147	139
20066	21311		Carrying case. Holds two K&M speaker/light stands 213, 214/6 etc. Made from black waterproof nylon with silk-screened K&M logo. Two inside compartments with cord closure and nylon handle.	22,71	27	27	26
20712	213 NEW MODEL 2009	BLK	A high quality steel speaker stand with zinc die-cast clamps for professional use. Infinitely variable height adjustment with a hand crank and push button system which prevents an uncontrolled reverse motion. There is an additional locking screw for extra safety. Extension tube diameter 35 mm, suitable for speakers and lighting crossbars with an integrated M10 thread connector.	185,36	221	224	213
20666	21302 NEW MODEL 2009	BLK	A high quality steel speaker stand with zinc die-cast clamps for professional use. Infinitely variable height adjustment with a hand crank and push button system which prevents an uncontrolled reverse motion. There is an additional locking screw for extra safety. Extension tube diameter 35 mm, suitable for speakers and lighting crossbars with an integrated M10 thread connector.	156,95	187	190	180
20494	24102	BLK	Corner speaker wall mount. A bolt-down wall mounting for installation in 90° corners. Made from solid rectangular steel tubing.	48,64	58	59	56
20129	24105	BLK	Mounting fork, Steel tube combination for 2 speakers, for tube diameter of 35 mm.	45,46	54	55	52
20662	24106 NEW	BLK	A new mounting fork for speakers with tubing diameter of 35 mm. The speaker fit is tight and snug due to two patented clamping mandrels. The weight of the speakers automatically straddles and fixes the clamping jaws. Suitable for loud speakers with connector diameters of 33 to 39 mm. TÜV (German Technical Supervisory Agency) approved for 2 x 25 kg weight max.	73,54	88	89	85
20679	24110	BLK	Screw-on wall mount with innovative, patented straddling bearing-anchors. Suitable for speakers with connector diameter of 35/37 mm. This mount provides simple attachment and guaranteed effective clamping of speaker in any position. Unit can be tilted to 22° in 11 settings, side adjustment + 90°. Resonance-optimised construction. Max. central load capacity 50 kg. Weight: 2,7 kg.	67,19	80	81	77
20128	241	BLK	Speaker wall mount, Made of solid rectangular steel. Interchangeable mounting bolt diameter 35 mm.	43,29	52	52	50
20663	24120 NEW MODEL 2009	BLK	The swivelling and tiltable wall mount holds your speaker at the angle you want. The mount has 11 different tilt settings moving through 22°. The swivel is adjustable to any angle. The patented expanding mandrel for loud speakers with cabinet interiors of diameter from 35 to 37 mm is tightened with a key for a non-wobble and low-resonance speaker fit.	132,05	157	160	152
20134	24180	BLK	Speaker wall mount, Two adjustable brackets 20 x 98 mm and 24 x 98 mm, tilt angle to 15°. Wall clearance 105 mm.	29,58	35	36	34
20137	24188	BLK	Speaker wall mount, Wall and ceiling bracket for Alesis Pro-Active 2.0 speakers, Adjustable to any angle by special swivel ball joint assembly.	29,79	35	36	34
20430	24195	BLK	Speaker wall mount, Wall and ceiling bracket for speakers, adjustable, additional security by wire cable. Wall clearance 271 mm.	33,76	40	41	39
20476	24150	BLK	Speaker wall mount, With a joint and a tube clamp.	69,03	82	84	79
20135	24185	BLK	Speaker wall mount, Mounts to walls and ceilings. Mounting plate 95 x 80 mm. Adjustable to any angle by special swivel ball joint assembly. Wall clearance: 175 mm.	25,57	30	31	29
20556	24400 #	SI	Beamer mount for ceilings	192,22	229	233	221
20557	24401 #	SI	Extension for beamer mount, model 24400	94,44	112	114	109
20559	24412 #	SI	Wallmount for flatscreen format 32-50"	69,37	83	84	80
20665	24428 NEW MODEL 2009	BLK	A versatile, new wall mount design for monitors max. 46". It can be used for the following sizes: VESA standards from 300 x 300 to 400 x 600 mm, maximum measurements 400 x 760 mm and minimum width 260 mm. The mount is a particularly easy and uncomplicated hanging system. Inadvertent removal is prevented by clamp screws. Max. weight 40 kg. The mount can be swivelled to 45° on either side and tilted to an angle of 15°.	183,86	219	222	211
	24465	BLK	Speaker wall mount, screw-on type wall mount to hold a JBL-Control 1 speaker. The mounted speaker can be swiveled sideways and tilted.	36,10	43	44	42
	24465	WHITE	Speaker wall mount, screw-on type wall mount to hold a JBL-Control 1 speaker. The mounted speaker can be swiveled sideways and tilted.	36,10	43	44	42
20520	24470 = DYN WMK-10	BLK	Speaker wall mount, Multi-purpose wall mount for speakers with universal adapter plate. The mounted speaker can be swiveled to the sides and tilted up to 30°. Easy mounting by convenient hooking in and screw locking.	74,38	89	90	86
20521	24471	BLK	Speaker wall mount, Multi-purpose wall mount for speakers. The mounted speaker can be swiveled to the sides and tilted up to 30°. Easy mounting by convenient hooking in and screw locking.	63,35	75	77	73
20522	24480	BLK	Speaker wall mount, Multi-purpose wall mount for speakers with universal adapter plate and large wall plate for heavy speakers. The mounted speaker can be swiveled to the sides and tilted up to 30°. Easy mounting by convenient hooking in and screw locking.	79,39	94	96	91

20523	24481	BLK	Speaker wall mount, Multi-purpose wall mount for speakers with large wall plate for heavy speakers. The mounted speaker can be swiveled to the sides and tilted up to 30°. Easy mounting by convenient hooking in and screw locking.	68,20	81	83	78
20174	29305 #	BLK	Speaker wall mount, Made of sturdy tubular steel. Mounting arm can be swiveled 180° and speaker holder diameter 35 mm can be tilted. Clearance 520 mm.	136,89	163	166	157
20030	195/8	BLK	Mounting adapter, Attachable to speakers. Slip-on adapter for speaker stands with tube diameter 35 mm.	19,72	23	24	23
20032	196 #	BLK	Flange adapter, Attachable to speakers. Slip-on adapter for speaker stands with tube diameter 35 mm.	15,21	18	18	17
20318	19654	BLK	Flange adapter, Can be inserted or screwed into speaker enclosure. For stands with tube diameter 35 mm.	3,34	4	4	4
20035	19656	BLK	Flange adapter, Can be inserted or screwed into speaker enclosure. For stands with tube diameter 35 mm.	9,19	11	11	11
20598	19674	BLK	Speaker tilt connector "ring lock" For speaker stands with tube diameter of 35 mm. A unique patented expanding mandrel system provides a tight and firm fit for the speaker. The moveable plastic splints separate the speaker from the stand creating a vibration-free connection. Easy to use ring lock.	51,48	61	62	59
20554	19685	BLK	Adapter for LCD/TFT screens, Adapter for attaching a small LCD/TFT screen to a stand using a swivel joint with a 3/8" thread. In compliance with VESA75 / VESA100, the attachment plate can easily be mounted on the stand with the prismatic connection.	20,73	25	25	24
20238	24281	BLK	Scew-on adapter, Attachable to speakers. Slip-on adapter for speaker stands with tube-diameter 35 mm. With 2 drill holes diam. 11 mm at intervals of 115 mm and locking device.	25,57	30	31	29
20038	19670	BLK	Speaker tilt connector, For speaker stands with tube diameter of 35 mm. Angle adjustable to 15°. Secured by locking screw.	32,43	39	39	37
20259	19672	BLK	Speaker Tilt connector, Connector with angle of 15°. For stands with tube diameter of 35 mm, secured by handknob. Flexible support for different speaker sizes.	28,92	34	35	33
20462	21326	BLK	Adapter sleeve, Polyamide. For speaker flanges with inside tube diameter 38 mm. May be attached to K&M speaker stands with tube diameter 35 mm.	1,59	2	2	2
20063	213/3	BLK	Extension rod, For speaker and light stands. One end has internal M10 thread, the other end has external M10 thread.	30,09	36	36	35
20067	21333	BLK	Distance rod, Connecting rod for satellite systems. Steel tubing.	15,38	18	19	18
13117	21334	BLK	Distance rod, Connecting rod for satellite systems with M20 bolt. Steel tubing.	18,21	22	22	21
20068	21336	BLK	Distance rod, Connecting rod for satellite systems. With spring-loaded locking screw and safety bolt. Steel tubing.	46,07	55	56	53
20069	21337	BLK	Distance rod, Steel tube combination to connect satellite systems. With M20 bolt to attach connector plate 24116 for precise fit.	46,07	55	56	53
20070	21338	BLK	Distance rod with hand crank, Solid steel tubing to connect satellite systems. Height-adjustment by hand crank. Extra safety features provided by additional push-button and locking screw to avoid uncontrolled reverse motion.	125,53	149	152	144
20071	21339	BLK	Distance rod with hand crank. Same as 21338, but with thread bolt M20 for connector plate 24116 for zero backlash and absolute vertical position.	139,29	166	169	160
20250	21347	BLK	Distance rod, Steel tube combination to connect satellite systems. With bottom M20 thread to attach connector plate 24116. Zero backlash and absolute vertical position. Height-adjustable by locking screw and »safety-pin«.	41,36	49	50	48
20561	21348	BLK	Distance rod, Steel rod combination for connecting satellite systems. With additional plastic adapter for a clearance-free fit. Height adjustable by locking screw and »safety pin«.	36,27	43	44	42
20590	21360	BLK	Distance rod "ring lock", Steel connecting rod for satellite systems. Both ends fitted with a unique patented expanding mandrel system for a tight and firm fit for the base and satellite speaker. Moveable plastic splints separate the speaker from the stand creating a vibration-free connection. Easy to use ring lock.	48,47	58	59	56
20591	21364	BLK	Distance rod "ring lock", Steel connecting rod for satellite systems. One end fitted with a unique patented expanding mandrel system for a tight and firm fit for the speaker. Moveable plastic splints separate the speaker from the stand creating a vibration-free connection. Easy to use ring lock. The other end of the rod features a threaded bolt M20 for connector plate 24116.	44,96	54	54	52
20592	21366	BLK	Distance rod "ring lock", Steel connecting rod for satellite systems. Height adjustment using a non-scratching locking screw and safety pin. Both ends fitted with a unique patented expanding mandrel system for a tight and firm fit for the base and satellite speakers. Moveable plastic splints separate the speaker from the stand creating a vibration-free connection. Easy to use ring lock.	73,54	88	89	85
20593	21367	BLK	Distance rod "ring lock", Steel connecting rod for satellite systems. Height adjustment using a non-scratching locking screw and safety pin. One end is fitted with a unique patented expanding mandrel system for a tight and firm fit for the speaker. Moveable plastic splints separate the speaker from the stand creating a vibration-free connection. Easy to use ring lock. The other end of the rod features a threaded bolt M20 for connector plate 24116.	59,67	71	72	69
20346	24116	BLK	Connector plate, Zinc die-cast plate. Attachable to speakers. Diameter 105 mm. Four 6.5 mm holes. May be used with distance rods with M20 bolt.	8,52	10	10	10
20263	24635 #	BLK	Light stand made with sturdy steel tubing. Base construction with U-profile. Extension tube diameter 35 mm. Height adjustment by locking screw and »safety pin« security lock. Comes with an aluminum crossbar to attach up to 8 spot lights.	126,20	150	153	145

	24635 NEW MODEL 2009	BLK	The standard lighting stand constructed from steel tubing has been significantly improved. The new legs with tubing diameter of 35 mm guarantee stability and safety. Lasered bore holes and durable, robust plastic saddle washers improve the coefficient of friction between the legs and braces, and prevent scratching of the finish. A compact clamp with the patented push-button system affords user-friendly stand height adjustment. The locking screw provides additional stability. The M10 thread adaptor can be used to attach the included crossbar.	126,20	150	153	145
20264	24637	BLK	Side cross bar, Attaches to K&M light stand 24635. Accommodates 4 spot lights. Light-weight aluminum tubing with tube-diameter 36 mm.	30,92	37	37	36
20714	24630 NEW MODEL 2009	BLK	The standard lighting stand constructed from steel tubing has been significantly improved. The new legs with tubing diameter of 35 mm guarantee stability and safety. Lasered bore holes and durable, robust plastic saddle washers improve the coefficient of friction between the legs and braces, and prevent scratching of the finish. A compact clamp with a patented push-button system affords user-friendly stand height adjustment. The locking screw provides additional stability. The integrated M10 thread adaptor can be used to attach the crossbars 213/9 and 21393.	91,76	109	111	106
20694	246/1 NEW MODEL 2009	BLK	High quality lighting stand for professional use. New die-cast zinc clamps and the larger aluminum leg tubing enhance safety. Height adjustment to any height is by means of a hand crank and push button system. The integrated M10 thread adaptor can be used to attach crossbars 213/9 and 21393.	259,08	308	313	298
20608	24620	BLK	Lighting stand, lightweight aluminum lighting stand with cross bar. Stable folding 3-leg construction. Height and feet adjust by an easy-to-use clamping lever. Additional safety pin ensures secure support. Cross bar with boreholes for up to 8 spotlights. Optional corresponding screw fitting set 24621 available.	93,27	111	113	107
20669	24625	BLK	Lighting stand, Easy to transport, lightweight aluminum lighting stand, extension rod with adapter to take a TV pin (inner extension tube diameter 28 mm). Stable tripod construction. Height adjustable with handy clamping levers and additional safety pin.	81,23	97	98	93
20711	24640 NEW MODEL 2009	BLK	Extending to over 4 m, this lighting stand is for professional use. The new zinc die-cast clamps and the larger steel leg tubing give this top of the range stand more stability. The infinitely variable non-marring height adjustment can be reinforced with two safety rings. A variety of crossbars may be attached using the M10 thread adaptor.	208,93	249	253	240
20538	26411		Carrying case, To store and transport two lighting/speaker stands 246/1. Sturdy nylon fabric, water-resistant. Two inside compartments and two parallel zip closures with large carrying straps. Black with green K&M logo.	31,59	38	38	36
20064	213/9	BLK	Crossbar, For light stands. Rectangular steel tubing. Attaches with M10 x 40 mm bolt and washer.	21,56	26	26	25
20072	21393	BLK	Crossbar, Attachable to light and speaker stands with extension tube diameter of 35 mm. With 4 screw fittings for spot lights.	44,63	53	54	51
20601	21394	BLK	Screw set, For crossbars. Includes 4 screw fittings.	16,55	20	20	19
20546	24516	ALU	TV pin, Male thread M10 x 17 mm. Aluminum, blank, diameter 16 mm, L: 46.5 mm. Suitable for flange 66290.	3,34	4	4	4
20434	24518	NI	TV pin, Female thread M10 x 35 mm. Steel, nickel finish, diameter 28/35 mm. L: 215 mm.	19,05	23	23	22
20433	24519	NI	TV pin, Female thread M10 x 34 mm. Aluminum blank, or steel nickel finish. Diameter 28 mm. L: 115 mm.	7,19	9	9	8
20422	24521	BLK	Reducer flange, Suitable for all K&M speaker stands, tube-diameter 35 mm. With threaded bolt M10 x 12 mm and a large, comfortable handknob. 24521-300-55 with 3/8" threaded bolt x 12 mm.	18,72	22	23	22
20266	24521	BLK	Reducer flange, Suitable for all K&M speaker stands, tube-diameter 35 mm. With threaded bolt M10 x 12 mm and a large, comfortable handknob. 24521-300-55 with 3/8" threaded bolt x 12 mm.	17,05	20	21	20
20415	24528	BLK	Reducer flange, Suitable for all K&M speaker stands, with female thread M10 and a large, comfortable handknob.	17,88	21	22	21
	26720	BLK	Monitor stand, Steel stand for monitors with 3-leg base, stable and solid. Height adjustable with a non-scratching locking screw and additional safety pin. internal cable routing possible.	68,36	81	83	79
20449	26740	BLK	Monitor stand, Stable steel stand for monitors with broad completely level round cast-iron base-diameter 450 mm. Rod combination height adjustable using clamping screw and safety splint. For the direct attachment of monitors with 3/8" threaded joint (thread length 12 mm) or to screw in a connector plate 205 x 245 mm for Genelec monitor 1030 or monitors by other manufacturers. Includes 4 thread points and 4 rubber knobs.	107,31	128	130	123
20450	26750	BLK	Speaker stand, Stable steel stand with broad completely level round cast-iron base-diameter 450 mm. Rod combination height adjustable using clamping screw and safety splint. Speaker will be fixed with flange adapter. Also available as monitor stand (Order No. 26740-000-55).	87,42	104	106	101
	26785	BLK	Steel stand for the Genelec 8000 monitor series. This stable elegant stand has a 420 x 420 mm cast base with an oversized rod combination. Gradual height adjustment is made by a superior positioning and clamping knob. Quick, uncomplicated mounting of the monitor is accomplished using the suspension device.	209,94	250	254	241
	26790	BLK	Design monitor stand, A steel monitor stand with a stable, elegant 480 x 480 mm cast base. Height 500 mm. There are three bearing plates (item 26792) available to match the monitor size.	174,67	208	211	201
	26790	BLK	Design monitor stand, A steel monitor stand with a stable, elegant 480 x 480 mm cast base. Height 650 mm. There are three bearing plates (item 26792) available to match the monitor size.	185,20	220	224	213
	26790	BLK	Design monitor stand, A steel monitor stand with a stable, elegant 480 x 480 mm cast base. Height 800 mm. There are three bearing plates (item 26792) available to match the monitor size.	192,39	229	233	221

	26792	BLK	Bearing plate for monitors, suitable for the design monitor stands 26790 and 26795. Size 240 x 5 x 200 mm. Includes 4 spikes and 4 rubber knobs.	31,09	37	38	36
20708	26792	BLK	Bearing plate for monitors, suitable for the design monitor stands 26790 and 26795. Size 320 x 5 x 280 mm. Includes 4 spikes and 4 rubber knobs.	39,11	47	47	45
20612	26792	BLK	Bearing plate for monitors, suitable for the design monitor stands 26790 and 26795. Size 420 x 5 x 380 mm mm. Includes 4 spikes and 4 rubber knobs.	55,83	66	68	64
20655	26794	BLK	Equipment tray, Stable large tray for hardware and equipment, consists of steel supports and wood board, size 970 x 400 mm. Attaches to the main tube of TV stands 26796, 26797 and 26798, i.e. stands with tubing diameter 76 mm.	136,73	163	165	157
20613	26795	BLK	Design monitor stand, Steel stand for monitors with a stable, elegant 480 x 480 mm cast base. This stand has an oversized rod combination and a superior positioning and clamping knob that allows gradual height adjustable. There are three bearing plates (item 26792) available to match the monitor size.	220,63	263	267	254
20625	26796	BLK	TV stand, Steel stand with mounting plate for TVs or screens with VESA standard mounting thread. Stable, elegant cast metal base, 420 x 420 mm, oversized rod combination, gradual height adjustable with locking screw. internal cable routing possible.	309,72	369	375	356
20560	26797	BLK	TV stand, Steel stand for flat screens max. 42". Stable, elegant cast metal base 420 x 420 mm, oversized rod combination, gradual height adjustable with locking screw. internal cable routing possible.	344,32	410	417	396
20378	21385	BLK	Adapter for 36 mm rod (inside) to M 12 outside	20,14	24	24	23
20432	66290	BLK	Holding flange for TV pin, For TV-pin diameter 28 mm and for 3/8" threaded bolt. Attaches to all K&M stands with tube-diameter 35 mm. Fits to TV-pin 24516. Zinc alloy with black finish.	64,85	77	78	75
20306	66350	BLK	Connection sleeve, Attaches to all K&M speaker stand, for TV-pin diameter 28 mm and M10 x 20 mm thread.	31,09	37	38	36
20547	68120 #	ZI	Wire rope, Without plastic coat, according to DIN 3055-FE-1770 SZ. diameter 4 mm, L: 1000 mm, surface galvanized. One side loop, other side with screw-lock hook 8 x 80 mm DIN 5299 C. Wire rope: Calculated breaking load: 10,1 kN; Minimum breaking load: 8,7 kN; Load capacity of hook: 230 kg.	16,05	19	19	18
20548	68210 #	ZI	Eye bolt, M10 x 17 DIN 580 C15.	4,85	6	6	6